KINGPIN SCREENS

AUTO TRIGGER RF (KP500)

Auto Trigger RF is produced to control your screen automatic. When you turn on your projector the screens goes down and when you turn it off the screen goes up. The function is that it measures the power load from you projector. When the load becomes starts or goes away, then the transmitter sends an RF-signal to the remote control system (KP300, sold separatly).

RF TRANSMITTER
The wireless remote control is of RF-type (Radio Frequency) and can send the signal app. 20 meters indoors. RF-signals don't need visual contact and can therefore be hidden behind panels or ceilings.

FRECUENCY RF
The transmitting frecuency is 433,92 Mhz

WORKING TEMPERATURE
The approved working temperature is +5 to +40 degree celcius.

ELECTRICITY
This system is CE-marked and suitable for 230 v power (230V/50-60 Hz). The fuse is 9 A.

CONNECTION
Auto Trigger RF are to be connected between your projector and the electric socket. The KP500 has to be paired with the remote control system KP300, see operation guide (KP300 are sold separatly or delivered together with an electric Kingpin Screen)

TECHNICAL SPECIFICATION: AUTO TRIGGER RF, KP500

Article number	Name	Weight net/gross (kg)	L x W x H Product (mm)	L x W x H Box (mm)
KP500	Auto Trigger RF	0,19/0,22	85x65x35	145x85x45